



SAFETY DATA SHEET

SECTION I — SUPPLIER & PRODUCT INFORMATION

Product Identification: Prime Colors-AX
Product Class: Elastic, acetoxy-based, neutral curing, single-component silicone sealant
Trade Name: Prime Colors-AX
DOT Shipping Name: N/A
Formula Version Number: 1
Original MSDS Preparation Date: 24 June 2013
Revised MSDS Preparation Date: 20 November 2015
Supplier Name: VJ Ventures, Inc. d.b.a. Prime Sealants
Supplier Address: 2950 Newmarket St., #101-158, Bellingham, WA 98226 USA
USASupplier Telephone: 1.360.656.5183
Supplier Fax: 1.360.335.6879
Supplier Emergency 24-Hour Telephone: 1.360.656.5183
Chemical Name: Contains silicone.
Hazardous Classification: This product requires no classification according to Chemical Hazard Information Profile standards (CHIP).
Other Hazards: This substance is not identified as a Persistent Bioaccumulative Toxic (PBT) substance.

SECTION II — PHYSICAL DATA

Appearance & Order: Paste; various colors; characteristic odor.
Flash Point: > 302° F (150° C)
Relative Density: ~1
Autoflammability: ~801° F (427° C)
VOC g/l: <30

SECTION III — FIRE AND EXPLOSION HAZARD DATA

Flash Point: > 302° F (150° C)

Extinguishing Media: Carbon dioxide. Dry chemical powder. Water spray. Alcohol or polymer foam. Suitable extinguishing media for the surrounding fire should be used.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Closed containers near to the fire should be cooled with water (spray). Container may burst upon heating.

Unusual Fire & Explosion Hazards: In combustion emits toxic fumes.

SECTION IV — REACTIVITY DATA

Stability: Stable under recommended transport or storage conditions.

Chemical Stability: Stable under normal conditions.

Stable under normal conditions.

Hazardous Reactions: Hazardous reactions will not occur under normal transport and storage conditions.

Conditions to Avoid: Humidity. Heat. Direct sunlight.

Incompatibility (materials to avoid): Water. Acids. Strong oxidising agents. Strong reducing agents.

Hazardous Decomposition Products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides. Silica.

SECTION V — SPILL OR LEAK PROCEDURES

Environmental Hazard: No data available on ecotoxicity values.

Spillage: Sinks in water. Non-volatile. Insoluble in water. Not biodegradable.

Waste Disposal Method: Dispose of as hazardous waste. Allow product to cure. Containers can be disposed of under the category commercial waste or municipal waste.

Environmental Precautions: Do not discharge into drains or rivers.

Notice: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION VI — HEALTH HAZARD INFORMATION

Eye Contact: There may be irritation and redness.

Skin Contact: There may be irritation and redness at the site of contact.

Inhalation: Product releases acetic acid during curing. After curing, product is odourless and indifferent.

Ingestion: Causes irritation to esophagus and stomach.

Chronic Hazard: Delayed effects can be expected after long-term exposure. Not listed by OSHA, NTP or IARC as a carcinogen.

First Aid Procedures/Skin Contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. In case of persisting irritation call in a physician. Where possible show the physician container or label.

First Aid Procedures/Eye Contact: After separating the eyelids immediately flush eyes thoroughly with plenty of water. In case eye irritation persists, consult an ophthalmologist.

First Aid Procedures/Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

Potential Hazards: This substance is not identified as a PBT substance nor does it pose any significant hazards requiring label warnings under Chemical Hazard Information Profile standards (CHIP).

SECTION VII — SPECIAL PROTECTION INFORMATION

Respiratory Protection: Respiratory protection not required. Breathing apparatus in the event of high concentration. Gas/vapour filter, type E: sulphur dioxide and other acid gases (EN141).

Hand Protection: Butyl gloves. Nitrile gloves. PVC gloves. Breakthrough time of the glove material > 1 hour.

Eye Protection: Safety glasses with side-shields.

Skin Protection: Protective clothing.

Personal Hygiene: Do not eat, drink or smoke during application. Avoid direct contact with the substance.

Engineering Control: Ensure there is sufficient ventilation of the area.

SECTION VIII — SUBSTANCES FOR WHICH STANDARDS HAVE BEEN SET

Chemical Safety Assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

PBT identification: This substance is not identified as a PBT substance.

UN Transportation Number: UN0000.